

USP™ BASE SHEET

USP™ BASE (M)

Technical Data Sheet

Product Name: USP™ BASE SHEET; USP™ BASE (M)

Classification: Fiberglass BUR Roof Membrane; UL Type G2

Product Description: USP™ Base Sheet/USP™ Base (M) is manufactured with a heavyweight, select fiberglass mat designed and constructed to be strong, while remaining wrinkle resistant. The strong glass mat is saturated with a high quality, non-filled asphaltic bitumen for a strong, durable yet uniformly consistent in roll out for ease of application. Designed for use as a base ply in hot mop, cold applied and torch applied roofing applications and specifications requiring ASTM D-4601 Type I/II base sheet.

Application Method: USP™ Base Sheet/USP™ Base (M) is applied using mechanical fasteners or hot asphalt in hot mop techniques.

Fastening Pattern: Fastening patterns vary according to desired uplift resistance. Always contact the U.S. Ply, Inc. Technical Services department to verify fastening pattern meets desired uplift resistance. Note: The fastening patterns and lay lines are different between USP™ Base Sheet and USP™ Base (M) because of the difference in product width. To avoid confusion, these products should not be mixed.

Approvals: Meets the requirements of ASTM D 4601 Type I/II. U.S. Ply products are listed or approved with Underwriter's Laboratories (UL) and Factory Mutual (FM). Contact U.S. Ply, Inc. for specific/applicable codes.

Product Data: USP™ Base Sheet (typical)
UL Designation: UL Type G2
Roll Dimensions: 108' x 36" (32.9m x 1m)
Area of roll ft²: 3 squares (324 ft²).
Weight: 80 lbs/roll (36.2 kg/m²)
Rolls per pallet: 20 per pallet
Lap Lines: 2", 4", 17"

Product Data: USP™ Base (M) (typical)
UL Designation: UL Type G2
Roll Dimensions: 97'-6" x 39-3/8" ((29.7m x 1m)
Area of roll ft²: 3 squares (319.8 ft²)
Weight: 71 lbs/roll (32.3 kg/m²)
Rolls per pallet: 25 per pallet
Lap lines: 2"; 9-5/16"; 12-7/16; 18-11/16"

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative.

U.S. PLY, INC.

A DANNY ADAIR COMPANY

Corporate Headquarters: P.O. Box 11740, Fort Worth, Texas 76110
TOLL-FREE: 866-PUSH-PLY (866) 787-4759 • Local: (817) 413-0103 • Fax: (817) 413-8221
Website: www.usply.com • Email: sales@usply.com

May 2007