

# Product Data Sheet

## DURAFLEX® G4FR SBS

<u>Physical Properties (ASTM D5147):</u>	<u>Test Results</u>	<u>ASTM D6163 Minimum Standard</u>
Tensile Strength (lbf/in), 0°F (MD/XMD)	120/110 lbf/in	70 lbf/in
Tensile Strength (lbf/in), 73°F (MD/XMD)	105/75 lbf/in	30 lbf/in
Elongation (% @ Max Load), 0°F, (MD/XMD)	4%	1%
Elongation (% @ Max Load), 73°F (MD/XMD)	3%	2%
Elongation (% @ 5% Max Load), 73°F (MD/XMD)	5/7	3%
Tear Strength (lbf), (MD/XMD), 73°F, minimum	105/85 lbf	35 lbf
Low Temperature Flexibility, (°F), maximum	0°F (-18°C)	0°F
Dimensional Stability, %, maximum	<0.2%	1%
High Temperature Stability, (°F)	250°F (121°C)	215°F
Granule Embedment, g/m <sup>2</sup> avg. loss	1.3	<2 g

DuraFlex® G4FR SBS is a fire-resistant, granule surfaced, premium SBS (Styrene-Butadiene-Styrene) mop or cold applied membrane. Manufactured with a fiberglass mat that is saturated and coated with high quality, asphaltic bitumen and SBS elastomers for a durable, flexible and easily maintainable membrane. It is designed for use as a cap sheet in modified bitumen and hybrid built-up roof systems.

### Product Name: DuraFlex® G4FR SBS

**Classification:** SBS Modified Bitumen Roof Membrane

**Application Method:** DuraFlex® G4FR SBS is applied using compatible hot asphalt or SBS cold adhesive.

**Approvals:** Meets ASTM D 6163 Type I, Grade G. DuraFlex® G4FR SBS is UL Classified with Underwriter's Laboratories (UL), is Factory Mutual (FM) Approved, and listed with Florida Building Code (FBC) FL-8077, and Texas Department of Insurance (TDI) RC-123. Contact U.S. Ply, Inc. for specific/applicable codes.

**Product Data:** DuraFlex® G4FR SBS (typical)

Thickness: 4.2 mm (166 mils)

Weight: 100 lbs/roll (45 kg/m<sup>2</sup>)

Roll Dimensions: 39 3/8" x 32' 9" (1m x 10m). Each roll is approximately 1 square applied.

**Green Standards Information:** DuraFlex® G4FR SBS contains approximately 6.5% of recycled materials by product weight. Materials are comprised of pre consumer recycled materials. The pre consumer recycled materials are derived from reclaimed non-hazardous coal combustion by-product waste which averts disposal of coal by-product waste in landfills or commercial dumps.

All values given are approximate and are subject to change without notice. There is no implied or express warranty given through these values or statements, nor are there any assertions that the product purchased has been individually tested to conform to these standards. Testing is performed on a random basis by "in-house" and independent "third party" evaluation for the purpose of classification and or approval. Acceptance, purchase and selection of these products are the sole responsibility of the buyer or buyer's representative. We assume no responsibility for coverage, performance or injuries resulting from use. Liability, if any, is limited to replacement of the product. NO OTHER WARRANTY OR GUARANTEE OF ANY KIND IS MADE BY U.S. PLY, INC. EXPRESSED OR IMPLIED; STATUTORY, BY OPERATION OF LAW, OR OTHERWISE, INCLUDING MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.



**CORPORATE HEADQUARTERS: P.O. BOX 11740, FORT WORTH, TEXAS 76110**

**TOLL-FREE: 866-PUSH-PLY (866) 787-4759 LOCAL: (817) 413-0103 • FAX: (817) 413-8221**  
WWW.USPLY.COM